

Meet your M1100.

About your M1100




Operation status

| Operations | | Actions |
|-----------------------|-----------------|--|
| Power button | Power on/off | Press and hold the Power button for 3 seconds to turn your M1100 on and off. |
| | Display wake-up | Press and release the Power button to wake up the display. |
| Battery Charge Colors | | STATStatus |
| | Black | The battery is fully charged. |
| | Red | The battery is critically low and the M1100 will shut down unless the battery is connected to the charger. |
| | Black | The M1100 is connected to an AC charger and charging. |
| | Black | The M1100 is connected via USB and charging. |

Device display

Screen



Status indicators

| | |
|--|--|
| | Home |
| | Network Signal Strength |
| | Data moving between mobile network and M1100 |
| | Roaming |
| | Unread messages |
| | M1100's Wi-Fi network |
| | Connected devices |
| | Ethernet connected |
| | USB tethered |

inseego

M1100

NOTE: Devices and software are constantly evolving - the screen images and icons you see here are for reference only.

WARNING!
Only use an approved charger to charge your M1100.

© 2019 Inseego Corp. All Rights Reserved
PN 90027154 R2
HH 081-0030-8157

Setting up your M1100

Turning your M1100 on/off

To turn your M1100 on, press and hold the **Power** button.

To turn it off, press and hold the **Power** button until you see the Powering off screen. Then select Shutdown and tap OK.

Press and release the **Power** button to wake up the display.

System requirements


Any device with Wi-Fi capability and an Internet browser .

Your M1100 is compatible with all major operating systems and the latest versions of browsers.

Finding the Wi-Fi name and password

Just tap **Wi-Fi Name/Password** on the **Home** screen.

The information for your M1100's primary network will be shown. Swipe left to see the info for your guest network.



Important: The default Admin password is the same as the primary network's default. To change either password, sign in to the M1100 Admin website (see **Accessing advanced settings**).

Connecting to the internet

On your device, open the list of available Wi-Fi networks. Select the M1100's primary or guest network and enter the password.

Managing Wi-Fi networks and connections

Your M1100 has 2 Wi-Fi networks, primary and guest, and lets you connect up to 15 Wi-Fi capable devices. For added security, share your guest network instead of your primary network.

The guest network is off by default. You can turn it on from either the M1100 or the Admin website by assigning it a band in Wi-Fi Settings> Band Selection. (See **Accessing advanced settings**).

Accessing advanced settings

You can access advanced settings and manage your M1100 from the Admin website:

1. Connect your Wi-Fi-capable device to the M1100's primary network (see **Connecting to the internet**).
2. Open a web browser on your enter **http://My.MiFi** or **http://192.168.1.1**.
3. Sign in with the M1100 Admin password. When you first get your M1100, this will be the same as your primary network's password. (**See Finding the Wi-Fi name and password.**)

Resetting your M1100

You can reset your M1100 to factory settings from the M1100 or from the Admin website.

NOTE: Resetting your M1100 will disconnect devices and reset network names and passwords.

To reset from the M1100:

1. Make sure your M1100 is on.
2. Remove the battery cover from the back of your M1100.
3. Insert an unfolded paper clip into the **Reset** hole and press until the M1100 screen shows **MiFi Resetting**.



To reset from the Admin website, go to **M1100 Settings > Backup and Restore**.

Support & more

Get help using your M1100

Use your Help app to get assistance right from your M1100.

Contact Inseego Customer service at www.inseego.com/support

More information

To access a **User Guide**, go to **www.inseego.com/support-documentation/** and find your device. Or, from the M1100 Admin website, select **My M1100 Home > Help & Support > Device Support Page & User Guide**.

Additional information

WARNING: DO NOT ATTEMPT TO SERVICE THE WIRELESS COMMUNICATION DEVICE YOURSELF. SUCH ACTION MAY VOID THE WARRANTY. THE MiFi MODEM IS FACTORY TUNED. NO CUSTOMER CALIBRATION OR TUNING IS REQUIRED. CONTACT INSEEGO TECHNICAL SUPPORT FOR INFORMATION ABOUT SERVICING YOUR WIRELESS COMMUNICATION DEVICE.

NOTE: The Radio Frequency (RF) emitter installed in your modem must not be located or operated in conjunction with any other antenna or transmitter, unless specially authorized by Inseego.